



simply pawfection

Heavenly frozen treat
for your dog

FREEZER OFFER 2022

IN PARTNERSHIP WITH AHT COOLING SYSTEMS SUPERMARKET (UK) LTD



✉ info@simplyicecream.co.uk

☎ +44 (0)1233 720922

📍 The Nook • Bonnington • Ashford • Kent • UK • TN25 7BA



AHT
a member of **DAIKIN** group

AHT Rio S Impulse Freezers



• Rio S 68 Baskets



• Rio S 100 Baskets



• Rio S 125 Baskets



• Rio S 150 Baskets



• Rio S 175 Baskets



68 · 100 · 125 150 · 175



Table Energy Efficiency Class		
Label	EEI from / to	
A	0	9.9
B	10	19.9
C	20	34.9
D	35	49.9
E	50	64.9
F	65	79.9
G	80	109.9
H	110	

Key Benefits:

- Excellent product visibility
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Adjustable thermostat

AHT Rio S	S 68	S 100	S 125	S 150	S 175
-----------	------	-------	-------	-------	-------

Technical characteristics

Gross capacity	132	238	322	405	488	L
Net capacity according to EN23953	102	190	258	327	396	L
Classification according to EN23953	7L1	7L1	7L1	7L1	7L1	
Ambient temperature	16°C to 35°C					°C
Maximum ambient humidity	70	70	70	70	70	%
Product temperature setting range	-14° to -23°C °C					

Electrical specifications

Rated voltage / frequency	230V/50Hz				V/Hz	
Consumption (at 30 °C)	1.6	1.85	2.45	3.2	4.0	kWh/24 h

Refrigeration characteristics

Refrigerant	R-290	Gas
-------------	-------	-----

Dimensions

Width outside	680	1000	1250	1500	1750	mm
Cabinet Height outside	880	880	880	880	880	mm
Glass Canopy Height	472.9	472.9	472.9	472.9	472.9	mm
Max. depth outside	650	650	650	650	650	mm

Weight

Net weight (excluding packaging)	49	59	66	74	81	kg
Gross weight (with packaging)	3	63	71	79	87	kg

Functioning Environment:

Our Freezers are designed to work at room temperature between 16° and 35° C and a maximum of 70% humidity (Class 7).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature. We recommend the use of air conditioning.

AHT
a member of **DAIKIN** group

Why purchase the AHT Rio S range when it comes to Impulse Display Chests?

- Very low energy consumption
- Galvanized steel inner liner, paired white so more robust than aluminium and also won't corrode.
- NO or very little icing in our cabinets (100% tight - no silicone joints in the 4 angles inside the cabinet)
- Very solid glass lids with frames moulded directly on the glass in one piece (no assembly - impossible to rip off the frame and the handle) Avoid Investment in new sets of glass lids for existing freezers
- The frame of our cabinet is in one piece, It is directly moulded on the cabinet during production (no assembly)
- The frame of our cabinet is very solid (ABS)
- Solid bottom and fixation of the wheels
- All components in the compressor room are placed on a drawer (easy to pull out and give easy access for repair)
- The Rio S is climate class 7, meaning it will work as expected in ambient conditions of up to 35°C and 70% humidity.

AHT
a member of **DAIKIN** group

AHT Coolpoint 50 & 100 CF

SMALL FORM FACTOR, EXCELLENT DISPLAY

AHT Coolpoint 50 & 100 CF	50 CF	100 CF	
Technical characteristics			
Net capacity	49	66	L
Climate Class	4	4	
Ambient temperature	16°C to 30°C	16°C to 30°C	°C
Maximum ambient humidity	70 %		
Product temperature setting range	-18° to -22°C	-18° to -22°C	°C
Electrical Specifications			
Rated voltage / frequency	230V/50Hz	230V/50Hz	V/Hz
Consumption (at 25 °C)	1.7	2.25	kWh/24 h
Refrigeration characteristics			
Refrigerant	R-290	R-290	Gas
Dimensions			
Width outside	480	530	mm
Cabinet Height outside (excluding canopy)	657	865	mm
Max. depth outside	464	480	mm
Weight			
Net weight (excluding packaging)	40	46	kg

Functioning Environment:

Our Freezers are designed to work at room temperature between 16° and 25° C and a maximum of 60% humidity (Class 3).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature. We recommend the use of air conditioning.



Key Benefits:

- Stylish design
- Low running costs
- Full LED illumination
- Light canopy on 100CF
- Adjustable shelving
- Removable gaskets
 - Lock
- Electronic controller
 - Adjustable feet

AHT
a member of **DAIKIN** group

COOLPOINT
AHT

AHT Coolpoint Can Freezer

PERFECT FOR PACKAGED
ICE CREAM AND LOLLIES

Key Benefits:

- Space for branding
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance



AHT Coolpoint PF Can Freezer 85

Net capacity according to EN 23953	72	L
Classification according to EN 23953	3L1	
Ambient temperature	16°C to 25°C	°C
Maximum ambient humidity	60	%
Product temperature setting range	-12°C to -22°C	°C

Electrical specifications

Rated voltage / frequency	230 V/ 50 Hz	V/Hz
Consumption (at 25 °C)	2	kWh/24 h

Refrigeration characteristics

Refrigerant	R600a	
-------------	-------	--

Dimensions

Width outside	570	mm
Height outside	830	mm
Max. depth outside	570	mm

Weight

Net weight (excluding packaging)	30	kg
----------------------------------	----	----

Functioning Environment:

Our Freezers are designed to work at room temperature between 16° and 25° C and a maximum of 60% humidity (Class 3).

Beyond these thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature. We recommend the use of air conditioning.

AHT
a member of **DAIKIN** group

COOLPOINT
AHT

AFTERCARE TROUBLESHOOTING GUIDE. PLEASE KEEP A COPY TO REFER TO AFTER PURCHASE

Operating your cabinet

- Do not make any technical changes to your cabinet. Otherwise there is a risk of injury or electric shock
 - Do not climb onto the lid or on top of the cabinet. There is a risk of injury due to material breakage
 - Do not exceed the load line on the cabinet this will impact performance.
- For scooping units all pan displays should be filled to ensure correct operation

Looking after your cabinet

- Your unit does not need much maintenance but simple steps will prolong the life of the unit and ensure it works correctly
 - Regularly wipe off the outside of the compressor grille with a dry cloth to remove any dust or debris build-up. You can also gently use a vacuum nozzle for this .
- NEVER USE A STEAM OR HIGH PRESSURE CLEANER
- Caution: Before removing the grille, always remove the plug from the power supply. All work on the power supply must be performed by suitably qualified staff

Defrost

- Ice build-up of 10mm indicates defrosting is required
- Empty the cabinet of all products
- Place a tray under the external drain hole (if the unit has one)
- To speed the process up you can place a container of warm water inside the unit
- Never use sharp implements to scrape as this may damage the unit
- When ice has melted away clean the unit with soap and water (no chemical detergent)
- Ensure the unit is completely dry before switching back on (to avoid ice build up and condensation)

Cabinet storage

- Be sure to defrost, clean and dry the unit fully. Leave lids/door open
- Cover the unit with a sheet (to protect against dust & dirt)

Troubleshooting

- In the unlikely event your unit is not operating to its optimum performance please ensure the following checks have been carried out before contacting the responsible service team.

Cabinet not running correctly:

- Check the electrical supply
- Check the thermostat setting
- Check the power supply connection

Cabinet not at the correct temperature:

- Check the air grille is not covered and at least 5cm is free around the freezer
- Check the cabinet is not in direct sunlight
- Check the lids/doors have not been left open
- Check the load line has not been exceeded
- Cabinet should be placed on a flat surface
- Site the cabinet away from other sources of heat
- Consider the limits of the climate classification (heat and humidity)
- After transportation please leave the cabinet 4 hours unplugged
- Cabinet will take 2-3 hours to reach temperature
- Keep the lids/doors closed whenever possible

AHT Service Hotline

Call - 01280 826600 (option 2)
AHT Cooling Systems (UK) Ltd
Unit C
Mill Court
Featherstone Road
Wolverton Mill
Milton Keynes
MK12 5EU

